

MIDNITE SOLAR'S NEW

DIY Series

MPPT INVERTER/CHARGERS

MidNite Solar's new DIY Series Inverter Charger with MPPT represents a versatile line of inverters/chargers at a great price!

MN3024DIY and MN5048DIY!

The MN3024DIY is a 3,000W, 24VDC inverter-charger that includes a built-in MPPT charge controller. The MN5048DIY is a 5,000W, 48VDC inverter-charger with built-in MPPT charge controller. Offering a simple, all-in-one installation and flexible programming, the new MidNite Solar Inverter/charger DIY Series will charge virtually any battery chemistry.

With excellent surge capability, the DIY Series will start the most demanding 120VAC loads. Perfect for your off-grid cabin or house, the DIY Series is designed to be affordable, dependable, and supported by the industry's best customer service personnel at MidNite Solar.



MIDNITE SOLAR'S NEW
DIY Series
 MPPT INVERTER/CHARGERS



APPLICATIONS:

Off grid - battery and PV or generator required
 Grid connected for backup - battery required

SPECIFICATIONS	MN3024DIY	MN5048DIY
System Voltage	24VDC	48VDC
AC		
Max Rated Power	3000W	5000W
Surge Power	4500W	7000W
Power Factor	1	1
Input Voltage	120VAC	120VAC
Input Voltage Range	90-140VAC +- 2% Adjustable	90-140VAC +- 2% Adjustable
Input/Output Frequency	60Hz	60Hz
Output Voltage	120VAC +- 5%	120VAC +- 5%
Output Waveform	Pure Sine Wave	Pure Sine Wave
Peak Efficiency	>95%	>95%
Max AC Charging Current	40A	40A
Internal Bypass Current	Up to 40A	Up to 63A
Conversion (Bypass and Invert)	10ms	10ms
SOLAR CHARGER		
Max PV Input/Output Power	1400W	5000W
Max PV Charging Current	60A	80A
Max PV Input Voltage	100V	500V
Algorithm	MPPT	MPPT
MPPT Voltage Range	30 - 95V	120 - 450V
BATTERY CHARGER		
Battery Type	Lead Acid or Lithium	Lead Acid or Lithium
Max AC Battery Charging Current:	40A	40A
Max PV Battery Charging Current:	60A	80A
Battery Voltage Range	20 - 33V DC	40 - 60V DC
Nominal Battery Voltage	24V	48V
ENVIRONMENTAL/MECHANICAL/WARRANTY		
Size	14.90"L x 11.03"W x 4.06"H	16.93"L x 13.31"W x 4.96"H
Operating Temperature	5°F ~ 131°F / -15°C ~ 55°C	5°F ~ 131°F / -15°C ~ 55°C
Storage Temperature	-13°F ~ 140°F / -25°C ~ 60°C	-13°F ~ 140°F / -25°C ~ 60°C
Humidity	5% ~ 95% (3 Layer Paint Protection)	5% ~ 95% (3 Layer Paint Protection)
Warranty	1 Year	1 Year

Manufactured for MidNite Solar in China.

